

DAC 2024 PRODUCT RANGE



Hauschild
SpeedMixer®

	DAC 150.1 / 150.3 FV	DAC 150.1 / 150.3 FVZ	DAC 250.3 FV	DAC 250.3 FVZ
Mixing capacity Min/Max [g] / [lb]:	100 - 150 / 0,22 - 0,33		150 - 250 / 0,33 - 0,55	
Mixing speed Min/Max [rpm]:	300 - 3500		300 - 2500	
Mixing time Min/Max [s]:	5s - 60s	5s - 300s	5s - 60s	5s - 300s
Voltage & Frequency:	230 V / 115 V - 50 Hz / 60 Hz			

	DAC 150.3 SP	DAC 250.3 SP
Mixing capacity Min/Max [g] / [lb]:	100 - 150 / 0,22 - 0,33	150 - 250 / 0,33 - 0,55
Mixing speed Min/Max [rpm]:	300 - 3500	300 - 2500
Mixing time Min/Max [s]:	5s - 600s	
Voltage & Frequency:	230 V / 115 V - 50 Hz / 60 Hz	

	DAC 400.1 FVZ	DAC 600.1 FVZ	DAC 700.1 FVZ	DAC 800.1 FVZ	DAC 1100.1 FVZ
Mixing capacity Min/Max [g] / [lb]:	250 - 400 / 0,55 - 0,88	300 - 600 / 0,66 - 1,32	350 - 700 / 0,77 - 1,54	400 - 800 / 0,88 - 1,76	300 - 1100 / 0,66 - 2,43
Mixing speed Min/Max [rpm]:	800 - 2750	800 - 2350	800 - 2100	800 - 1950	800 - 1600
Mixing time Min/Max [s]:	5s - 600s				
Voltage & Frequency:	230 V / 115 V - 50 Hz / 60 Hz				

	DAC 400.1 FVZ LR	DAC 600.1 FVZ LR	DAC 700.1 FVZ LR	DAC 800.1 FVZ LR
Mixing capacity Min/Max [g] / [lb]:	250 - 400 / 0,55 - 0,88	300 - 600 / 0,66 - 1,32	350 - 750 / 0,77 - 1,54	400 - 800 / 0,88 - 1,76
Mixing speed Min/Max [rpm]:	800 - 2300	800 - 2100	800 - 1850	800 - 1750
Mixing time Min/Max [s]:	5s - 600s			
Voltage & Frequency:	230 V / 115 V - 50 Hz / 60 Hz			

	DAC 400.2 VAC-P	DAC 600.2 VAC-P	DAC 700.2 VAC	DAC 800.2 VAC-P	DAC 1100.2 VAC-P
Mixing capacity Min/Max [g] / [lb]:	250 - 400 / 0,55 - 0,88	300 - 600 / 0,66 - 1,32	350 - 700 / 0,77 - 1,54	400 - 800 / 0,88 - 1,76	300 - 1100 / 0,66 - 2,43
Mixing speed Min/Max [rpm]:	800 - 2500	800 - 2350	800 - 2100	800 - 1950	800 - 1600
Mixing time Min/Max [s]:	5s - 600s				
Voltage & Frequency:	230 V / 115 V - 50 Hz / 60 Hz				

	DAC 400.2 VAC-P LR	DAC 600.2 VAC-P LR	DAC 700.2 VAC LR	DAC 800.2 VAC-P LR
Mixing capacity Min/Max [g] / [lb]:	250 - 400 / 0,55 - 0,88	300 - 600 / 0,66 -	350 - 700 / 0,77 - 1,54	400 - 800 / 0,88 -
Mixing speed Min/Max [rpm]:	800 - 2300	1,32 800 - 2100	800 - 1850	1,76 800 - 1750
Mixing time Min/Max [s]:	5s - 600s			
Voltage & Frequency:	230 V / 115 V - 50 Hz / 60 Hz			

	DAC 3000 HP	DAC 5000 HP	DAC 10000 HP
Mixing capacity Min/Max [g] / [lb]:	1500 - 3000 / 3,31 - 6,61	2500 - 5000 / 5,51 - 11,02	3500 - 10000 / 7,72 - 22,05
Mixing speed Min/Max [rpm]:	50 - 1000	50 - 800	50 - 800
Mixing time Min/Max [s]:	5s - 600s (Pro version up to 1800s)		
Voltage & Frequency:	400 VAC / 480 VAC - 50 Hz / 60 Hz		

	DAC 3000 VAC-P	DAC 5000 VAC-P	DAC 10000 VAC-P
Mixing capacity Min/Max [g] / [lb]:	1500 - 3000 / 3,31 - 6,61	2500 - 5000 / 5,51 - 11,02	3500 - 10000 / 7,72 - 22,05
Mixing speed Min/Max [rpm]:	50 - 900	50 - 800	50 - 600
Mixing time Min/Max [s]:	5s - 600s (Pro version up to 1800s)		
Voltage & Frequency:	400 VAC / 480 VAC - 50 Hz / 60 Hz		



2024 SMART-DAC PRODUCT RANGE



Hauschild
SpeedMixer[®]

	SMART DAC 400.3 FVZ LR	SMART DAC 600.3 FVZ LR	SMART DAC 700.3 FVZ LR	SMART DAC 800.3 FVZ LR
Mixing capacity Min/Max [g] / [lb]:	250 - 400 / 0,55 - 0,88	300 - 600 / 0,36 - 1,32	350 - 700 / 0,77 - 1,54	400 - 800 / 0,88 - 1,76
Mixing capacity Max [ml] / [gal]:	1000 / 0,26	1000 / 0,26	1000 / 0,26	1000 / 0,26
Mixing speed Min/Max [rpm]:	50 - 2400	50 - 2200	50 - 2000	50 - 1850
Mixing time Min/Max [s]:	5s - 600s (Pro version up to 1800s)			
Voltage & Frequency:	230 V / 115 V - 50 Hz / 60 Hz			

	SMART DAC 250.4 VAC-P LR	SMART DAC 400.4 VAC-P LR	SMART DAC 600.4 VAC-P LR	SMART DAC 700.4 VAC-P LR	SMART DAC 800.4 VAC-P LR
Mixing capacity Min/Max [g] / [lb]:	100 - 250 / 0,33 - 0,55	250 - 400 / 0,55 - 0,88	300 - 600 / 0,66 - 1,32	350 - 700 / 0,77 - 1,54	400 - 800 / 0,88 - 1,76
Mixing capacity Max [ml] / [gal]:	400 / 0,10	1000 / 0,26	1000 / 0,26	1000 / 0,26	1000 / 0,26
Mixing speed Min/Max [rpm]:	50 - 2500	50 - 2400	50 - 2200	50 - 2000	50 - 1850
Mixing time Min/Max [s]:	5s - 600s (Pro version up to 1800s)				
Voltage & Frequency:	230 V / 115 V - 50 Hz / 60 Hz				

	SMART DAC 1100.3 FVZ	SMART DAC 1500.3 FVZ	SMART DAC 2000.3 FVZ
Mixing capacity Min/Max [g] / [lb]:	300 - 1100 / 0,66 - 2,42	700 - 1500 / 1,34 - 3,30	1000 - 2000 / 2,20 - 4,41
Mixing capacity Max [ml] / [gal]:	2000 / 0,53	3300 / 0,87	3300 / 0,87
Mixing speed Min/Max [rpm]:	50 - 1700	50 - 1400	50 - 1200
Mixing time Min/Max [s]:	5s - 600s (Pro version up to 1800s)		
Voltage & Frequency:	230 V / 115 V - 50 Hz / 60 Hz		

	SMART DAC 1100.4 VAC-P	SMART DAC 1500.4 VAC-P	SMART DAC 2000.4 VAC-P
Mixing capacity Min/Max [g] / [lb]:	300 - 1100 / 0,66 - 2,42	700 - 1500 / 1,34 - 3,30	1000 - 2000 / 2,20 - 4,41
Mixing capacity Max [ml] / [gal]:	2000 / 0,53	3300 / 0,87	3300 / 0,87
Mixing speed Min/Max [rpm]:	50 - 1700	50 - 1400	50 - 1200
Mixing time Min/Max [s]:	5s - 600s (Pro version up to 1800s)		
Voltage & Frequency:	230 V / 115 V - 50 Hz / 60 Hz		

	SMART DAC 1100.3 FVZ LR	SMART DAC 1500.3 FVZ LR	SMART DAC 2000.3 FVZ LR
Mixing capacity Min/Max [g] / [lb]:	300 - 1100 / 0,66 - 2,42	700 - 1500 / 1,34 - 3,30	1000 - 2000 / 2,20 - 4,41
Mixing capacity Max [ml] / [gal]:	3750 / 1,00		
Mixing speed Min/Max [rpm]:	50 - 1200	50 - 1100	50 - 1000
Mixing time Min/Max [s]:	5s - 600s (Pro version up to 1800s)		
Voltage & Frequency:	230 V / 115 V - 50 Hz / 60 Hz		

	SMART DAC 1100.4 VAC-P LR	SMART DAC 1500.4 VAC-P LR	SMART DAC 2000.4 VAC-P LR
Mixing capacity Min/Max [g] / [lb]:	300 - 1100 / 0,66 - 2,42	700 - 1500 / 1,34 - 3,30	1000 - 2000 / 2,20 - 4,41
Mixing capacity Max [ml] / [gal]:	3750 / 1,00		
Mixing speed Min/Max [rpm]:	50 - 1200	50 - 1100	50 - 1000
Mixing time Min/Max [s]:	5s - 600s (Pro version up to 1800s)		
Voltage & Frequency:	230 V / 115 V - 50 Hz / 60 Hz		

